

Safety Data Sheets

1. Identification

Product Name : SS21 ink Light Cyan
Order No. : SPC-0501LC-4 / SPC-0588LC-4/ SS21-LC-60-4
General Use : Ink for ink jet printer
Product Description : Solvent pigment ink
Manufacture
Company Name : Mimaki Engineering Co., Ltd.
Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN
Telephone No. : +81-268-64-2413
Importer / Distributor Established in USA
Company Name : MIMAKI USA, INC.
Address : 4851 Thurmon Tanner Parkway, STE 100 Flowery Branch, GA
30542, U.S.A.
Telephone No. : +1-678-730-0170
Emergency Telephone No. : +1 866 928 0789 (within United States only, Toll free)
+1 215 207 0061

2. Hazards Identification

[GHS Classification]

Physical Hazards

Flammable Liquids : Category 4

Health Hazards

Eye Damage / Irritation : Category 1

Toxic to Reproduction : Category 1B

Specific Target Organ Toxicity : Category 2
(Single Exposure)

Specific Target Organ Toxicity : Category 2
(Repeated Exposure)

The above list does not include category being non-classifiable or not-applicable.

[GHS Label Elements]

Safety Data Sheets

Symbol



Signal Word

Danger

Hazard Statements

H227 Combustible liquid.

H318 Cause serious eye damage.

H360 May damage fertility or the unborn child.

H371 May cause damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

[Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's operation manual before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from open flames and other ignition sources. No smoking.

P260 Do not breathe gas/mist/vapours.

P264 Wash hands and eyes thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

[Response]

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.

(P305+)P310 (IF IN EYES) Immediately call a POISON CENTER or doctor/physician.

P314 Get medical advice/attention if you feel unwell.

P370+P378 In case of fire: Use foam, carbon dioxide, dry chemical for extinguish.

[Storage]

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

[Disposal]

P501 Dispose of contents/container in accordance with local/regional/national/international regulation (to be specified).


NFPA Rating (scale 0 – 4)

Health = 3

Flammability = 2

Instability = 0

Special = None



CANADIAN WHMIS SYMBOLS



3. Composition / Information on Ingredients

Mixtures

Safety Data Sheets

No	Chemical Name	Wt%	CAS No.
1	Glycol ether solvents	75-85	Trade Secret
2	Lactone solvent series	10-20	Trade Secret
3	Vinyl resin	1-5	Trade Secret
4	Pigment	0.1-1	Trade Secret
5	Corrosion inhibitor	0.1-1	Trade Secret

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

Description of first aid measures

- Eye Contact** : If this product comes in contact with the eyes:
Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
- Skin Contact** : If skin or hair contact occurs:
Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
- Inhalation** : If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
- Ingestion** : Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire Fighting Measures

- Flammable Properties** : Flash point 71.1 degree C
Auto Ignition Temperature: 169 degree C

Safety Data Sheets

Explosive Limit : 2% to 33.0%

Extinguishing Media : Foam, Dry chemical powder, BCF (where regulations permit),
Carbon dioxide, Water spray or fog - Large fires only.

Unsuitable Extinguishing Media : Do not scatter spilled material with high-pressure water streams.

Special hazards arising from the substrate or mixture

Fire : None known.

Incompatibility

Special protective equipment and precautions for fire-fighters

Fire Fighting : Alert Fire Brigade and tell them location and nature of hazard.
Wear full body protective clothing with breathing apparatus.
Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools.
DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location.
If safe to do so, remove containers from path of fire.

Fire/Explosion Hazard : Combustible.
Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit irritating/ toxic fumes. May emit acrid smoke. Mists containing combustible materials may be explosive.
May emit poisonous fumes.
May emit corrosive fumes.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

See section 8.

Environmental precautions

See section 12.

Methods and material for containment and cleaning up

Minor Spills : Remove all ignition sources. Clean up all spills immediately.
Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Contain and absorb spill with sand, earth, inert material or

Safety Data Sheets

Major Spills	<p>vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.</p> <p>: Moderate hazard.</p> <p>Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.</p>
--------------	---

7. Handling and Storage

Precautions for Safe Handling	<p>: Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately.</p>
Conditions for Safe Storage	<p>: Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.</p>
Storage incompatibility	<p>: None known.</p>

8. Exposure Controls / Personal Protection

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

Safety Data Sheets

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
OSHA-PELs	Pigment	Trade secret	0.1 mg/m ³ / 1mg/m ³	Not Available	Not Available	(as Cu) / (as Cu);Dusts and mists

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Vinyl resin	Trade secret	120 mg/m ³	1,300 mg/m ³	7,900 mg/m ³
Lactone solvent series	Trade secret	3.6 mg/m ³	39 mg/m ³	310 mg/m ³

Ingredient	Original IDLH	Revised IDLH
Pigment	Not Available	Not Available
Vinyl resin	Not Available	Not Available
Glycol ether solvents	Not Available	Not Available
Lactone solvent series	Not Available	Not Available
Corrosion inhibitor	Not Available	Not Available

Exposure Controls

Occupational Exposure Controls

Appropriate

: General exhaust is adequate under normal operating conditions. If

Engineering Controls

risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

Personal Protection

Respiratory

: Consult with a health and safety professional for specific respirators appropriate for your use.

Protection



Hand Protection

: Wear chemical protective gloves, e.g. PVC.



Eye Protection

: Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.



Safety Data Sheets

Skin Protection : Wear safety footwear or safety gumboots, e.g. Rubber. Overalls.



P.V.C. apron.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance: Light Cyan liquid

Physical state	Liquid	Relative density (Water = 1)	0.964
Odour	Slight	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	169
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point /freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	176-204	Molecular weight (g/mol)	Not Available
Flash point (°C)	71.1 (closed cup)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Combustible	Oxidising properties	Not Available
Upper Explosive Limit (%)	33	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	2	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	2.67	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

10. Stability and Reactivity

Reactivity : Stable under normal conditions of use.

Chemical Stability : Unstable in the presence of incompatible materials.

Product is considered stable.

Possibility of Hazardous : Hazardous polymerisation will not occur.

Reactions

Conditions to Avoid : See section 7.

Safety Data Sheets

Incompatible Materials : See section 7.
 Hazardous : See section 5.
 decomposition products

11. Toxicological Information

Information on toxicological effects

Inhaled : The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Ingestion : The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence.

Skin Contact : The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives.
 Open cuts, abraded or irritated skin should not be exposed to this material
 Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Eye : If applied to the eyes, this material causes severe eye damage.

Chronic : Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.
 Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.

Ingredient	TOXICITY	IRRITATION
As a product	Not Available	Not Available
Pigment	Not Available	Not Available
Vinyl resin	Not Available	Not Available
Glycol ether solvents	Not Available	Not Available

Safety Data Sheets

Lactone solvent series	Not Available	Not Available
Corrosion inhibitor	Not Available	Not Available

Acute Toxicity : Data Not Available to make classification.
 Skin : Data Not Available to make classification.
 Irritation/Corrosion
 Serious Eye : Data available to make classification.
 Damage/Irritation
 Respiratory or Skin : Data Not Available to make classification.
 sensitisation
 Mutagenicity : Data Not Available to make classification.
 Carcinogenicity : Data Not Available to make classification.
 Reproductivity : Data available to make classification.
 STOT - Single Exposure : Data available to make classification.
 STOT - Repeated : Data available to make classification.
 Exposure
 Aspiration Hazard : Data Not Available to make classification.

12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it. Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
Pigment	LC50	96	Fish	4610.012mg/L	3
	EC50	96	Algae or other aquatic plants	30524.744mg/L	3
	EC50	384	Crustacea	1049.064mg/L	3
Glycol ether solvents	LC50	96	Fish	713.772mg/L	3
	EC50	96	Algae or other aquatic plants	4246.290mg/L	3
	EC50	384	Crustacea	163.553mg/L	3
Lactone solvent series	LC50	96	Fish	220mg/L	1
	EC50	48	Crustacea	>500mg/L	1
	EC50	96	Algae or other aquatic plants	16.400mg/L	3

Safety Data Sheets

	EC20	72	Algae or other aquatic plants	=14mg/L	1
	NOEC	24	Fish	=5mg/L	1
Corrosion inhibitor	LC50	96	Fish	1514.080mg/L	3
	EC50	48	Crustacea	374mg/L	2
	EC50	96	Algae or other aquatic plants	61.454mg/L	3
	EC50	504	Crustacea	59.8mg/L	2
	NOEC	504	Crustacea	3.99mg/L	2

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances – Ecotoxicological

Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated)

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Pigment	HIGH	HIGH
Glycol ether solvents	LOW	LOW
Lactone solvent series	LOW	LOW
Corrosion inhibitor	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
Pigment	LOW (BCF = 11)
Glycol ether solvents	LOW (LogKOW = 0.0093)
Lactone solvent series	LOW (BCF = 1.8)
Corrosion inhibitor	LOW (LogKOW = -0.6047)

Mobility in soil

Ingredient	Mobility
Pigment	LOW (KOC = 10000000000)
Glycol ether solvents	LOW (KOC = 10)
Lactone solvent series	LOW (KOC = 7.134)
Corrosion inhibitor	HIGH (KOC = 1)

13. Disposal Considerations

Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body of water.

Disposal Methods : Dispose in accordance with all applicable regulations.

Safety Data Sheets

Disposal of Contaminated Packaging : Empty containers may contain product residue. Dispose in accordance with all applicable regulations.

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

Labels Required : Marine Pollutant; NO

Land transport (DOT) : NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS.
*1

Air transport (ICAO-IATA / DGR) : NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS.

Sea transport (IMDG-Code / GGVSee) : NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS.

Transport in bulk according to Annex II of MARPOL and the IBC code : Not Applicable

*1 Class combustible liquid (NA1993), Packing group III for quantities of 450 liters (119 gallons) or more; not regulated for smaller quantities

15. Regulatory Information

Safety, health and environmental regulations / legislation specific for the substance or mixture
PIGMENT IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - California - Proposition 65 - Priority List for the Development of MADLs for Chemicals Causing Reproductive Toxicity
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)
US - California Permissible Exposure Limits for Chemical Contaminants
US - California Proposition 65 - Carcinogens
US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens
US - Hawaii Air Contaminant Limits
US - Idaho - Limits for Air Contaminants
US - Michigan Exposure Limits for Air Contaminants
US - Minnesota Permissible Exposure Limits (PELs)
US - Oregon Permissible Exposure Limits (Z-1)

Safety Data Sheets

US - Pennsylvania - Hazardous Substance List
US - Rhode Island Hazardous Substance List
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - Washington Permissible exposure limits of air contaminants
US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US Clean Air Act - Hazardous Air Pollutants
US CWA (Clean Water Act) - Priority Pollutants
US CWA (Clean Water Act) - Toxic Pollutants
US EPCRA Section 313 Chemical List
US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens
US OSHA Permissible Exposure Levels (PELs) - Table Z1
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

VINYL RESIN IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

GLYCOL ETHER SOLVENTS ARE FOUND ON THE FOLLOWING REGULATORY LISTS

US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)
US - Pennsylvania - Hazardous Substance List
US Clean Air Act - Hazardous Air Pollutants
US EPCRA Section 313 Chemical List
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

LACTONE SOLVENT SERIES ARE FOUND ON THE FOLLOWING REGULATORY LISTS

US Drug Enforcement Administration (DEA) List I and II Regulated Chemicals
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

CORROSION INHIBITOR IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	Yes
Fire hazard	Yes

Safety Data Sheets


Pressure hazard	No
Reactivity hazard	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported.

State Regulations

US. CALIFORNIA PROPOSITION 65

	<p>: WARNING:</p> <p>This product can expose you to chemicals including Cumene, Ethylbenzene, Vinyl chloride, Vinyl acetate, Ethylene glycol monoethyl ether, Ethylene glycol monomethyl ether, Acetaldehyde, Methanol and Benzene which are known to the State of California to cause cancer/ birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.</p>
---	--

Inventory

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	Y
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	N
USA - TSCA	Y

Legend: Y = All ingredients are on the inventory.

N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets).

16. Other Information

Other Information

This information is furnished without warranty, express or implied, except that it is accurate to



Product Name: SS21 ink Light Cyan
SDS No. 037-S0810517
First issue: 2026/04/08
Revised:

Safety Data Sheets

the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.